

## 2-Bay SATA to USB 3.0/eSATA/Firewire 800 Enclosure (Silver)



The **MobileRAID MR2CT+** is a hardware RAID embedded enclosure provides high performance storage for creative professional with a transfer speed of 200MB/s. The embedded Hardware RAID design provides offload of complex RAID calculation from the computer to the unit, allowing high performance throughput to eSATA and USB 3.0 (backward compatible with USB 2.0). Firewire 800 port (backward compatible with Firewire 400) allows connection with MAC computer that does not have eSATA or USB port. Triple interface setup provides easy connection to various computer operating systems. Since RAID engine is embedded inside the enclosure, there is no OS compatibility issue. With support of RAID 0 and RAID 1, MR2CT+ allows user to choose from fast performance on RAID 0 or hard drive redundancy protection on RAID 1. With hot-swappable hard drive design, and high performance transfer rate to support various audio and video editing problems, MR2CT+ is the ideal storage RAID tower for high-end computing.

### Features

- 2 bay Hardware RAID enclosure support RAID 1 or RAID 0.
- Hardware RAID embedded to the enclosure to eliminate OS compatibility issues.
- Triple Host Interfaces: USB 3.0, eSATA, Firewire 800 (backward compatible with USB 2.0 and Firewire 400).
- LED status and buzzer for RAID management and monitor system status.
- Features two RAID modes, including RAID 0 or RAID 1 for redundancy or performance.
- Support JBOD for individual drives access and spanning for simple storage expansion\*.
- Supports the latest 4TB hard drive. Up to 8TB in storage capacity.
- Supports Windows 7, 2000, XP, Vista, Windows Server 2003 and 2008, MAC OS X and Linux.

### Specifications

## Model

MR2CT+

## Form Factor

Compact Tower

## RAID Level

0, 1, JBOD\* and Spanning \* Support over Firewire 800 & eSATA. eSATA port multiplier required.

## Maximum Capacity

8TB

## Host Interface

USB 3.0, eSATA, Firewire 800 (1394b) (Backward compatible with USB 2.0 and Firewire 400 (1394a)).

## Drive Interface

2 x 3.5" SATA, Hot-swappable Tray

## Cooling Fan

1.6" Ball Bearing

## Power Supply

80W (110V~240V)

## Control Interface

RAID Dial

## Status Indicator

Link, Status and Power LEDs

## Dimension (in)

4.8"W x 8.0"D x 4.0"H

## Weight (lb)

3.8 lb

## Safety Regulations

CE, FCC

## Limited Warranty

2 Years

## Package Contents

MR2CT+ (1) Power Cord (1) USB 3.0 Cable (1) eSATA Cable (1) Firewire 1394b (1) Quick Installation Manual (1)

